Fleetguard® | Product Specification

LF3400

Lube, Full-Flow Spin-On

Fleetguard® LF3400 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.



BPV OPENING DP	9.42747 PSI
Thread Size	3/4-16 UNF-2B
Media Type	StrataPore
Length	3.62 inch
Largest OD	3.68 inch
Gasket Inside Diameter	2.44 inch
Gasket OD	2.76 inch
Seam OD	3.681 in
Efficiency	60%
Standpipe	NO

This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved