



Product Specification

LF689

Lube, Full-Flow Spin-On

Fleetguard® LF689 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



BPV OPENING DP	10.007622 PSI
Thread Size	3/4-16 UNF-2B
Gasket OD	2.83 inch
Gasket Inside Diameter	2.46 inch
Length	4.22 inch
Largest OD	3.79 inch
Seam OD	3.787 in
Efficiency	95%
Standpipe	NO
Length / Overall Height	4.22 inch
Anti Drain Back Valve	Yes
Hydrostatic Burst Minimum	203.0 psi
Pressure Valve	Yes

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved