Fleetguard® | Product Specification

WF2051

Water, Spin-On

Choose Fleetguard® WF2051 DCA2 water filter with chemicals for coolant system protection that provides filtration and additive reinhibition. DCA2 water filters are designed for use with Fleetcool, Fleetcool EX or similar technology.



COOLANT ADDITIVE FORM	PELLET
Thread Size	11/16-16 UN-2B
Length	4.16 inch
Largest OD	3.67 inch
Additive Base	DCA2
Gasket Inside Diameter	2.46 inch
Gasket OD	2.83 inch
Seam OD	3.692 in
Chemical Additive	DCA2 (MODIFIED)

This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Cummins Filtration customers "as is" without any warranties,

express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved