Fleetguard® | Product Specification

WF2053

Water, Spin-On

Fleetguard® WF2053 water spin-on filter with cellulose media provides a convenient and reliable method for delivering immediate release DCA2 additive into the cooling system to improve performance and extend coolant service life.



COOLANT ADDITIVE FORM	PELLET
Thread Size	11/16-16 UN-2B
Length	5.40 inch
Largest OD	3.67 inch
Additive Base	DCA2
Gasket Inside Diameter	2.46 inch
Gasket OD	2.83 inch
Seam OD	3.686 in
Chemical Additive	DCA2 (MODIFIED)

This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Cummins Filtration customers "as is" without any warranties,

express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved