

RECIPROCATING SAWS

Performance:

Power: 1 hp (0.75 kW)
Strokes per Minute: 1,800
Stroke Length: 0.6" (15 mm)

Features:

Lockoff Trigger Start
Variable Speed
Swivel Air Inlet



1300

Reciprocating Saw

Model Number	Stroke Length		Strokes per Minute	Power		Weight		Length		Air Consumption	
	in	mm		hp	kW	lb	kg	in	mm	scfm	l/s
1300	0.6	15	1800	1	0.7	7.8	3.5	17.2	437	35	17

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Swivel Air Inlet • 2 Blades • Protective Boot

Accessories: Reciprocating Saw Accessories, see pages 89 – 90

Performance:

Strokes per Minute: 10,000
Stroke Length: 0.375" (10 mm)
Cuts up to 1/8" (3 mm) mild steel

Features:

Lock-off lever start
Low vibration
360° Adjustable Exhaust Deflector
Dual chuck accepts: standard air saw blades AND reciprocating saw blades, up to 0.040" thick



RS10K

Reciprocating Saw

Model Number	Stroke Length		Strokes per Minute	Weight		Length		Air Consumption	
	in	mm		lb	kg	in	mm	scfm	l/s
RS10K	0.375	10	10000	1.53	0.69	9.4	240	8.4	4.0

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Swivel Air Inlet • Protective Boot

Accessories: Reciprocating Saw Accessories, see pages 89 – 90

Reciprocating Saw Blades



1815



1816

Reciprocating Saw Blades

Part Number	Length		Teeth Per Inch
	in	mm	
For Use on Model 1300 & RS10K			
1815B	6	150	10
1810	6	150	14
1813	4	100	14
1811	6	150	18
1812	4	100	18
1814	6	150	24
1816	6	150	6
1819	12	300	6



1823

Air Saw Blades

Part Number	Length		Teeth Per Inch
	in	mm	
For Use on Model RS10K			
1823	3.7	94	18
1824B	3.7	94	24
1825	3.7	94	32

Packaged in Cartons of 5



SAFETY PRECAUTION: Read and follow all safety and operating instructions.

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1